



YACHTING

Finally a clean drive
throughout the season



- > New generation selfpolishing antifouling for drives, flaps and other light metal components
- > Unique effect against fouling
- > Outstanding hiding power



NEW

AQUALINE OPTIMA A new generation selfpolishing antifouling for drives, propellers, flaps and other light metal components below the waterline. Aqualine Optima provides an outstanding fouling protection and has excellent hiding power. Try Aqualine Optima and keep your drive clean throughout the entire season!

COVERAGE per coat	CLEANING	DRYING TIME			COLOUR
		23°C	15°C	10°C	
10 m ² /ltr.	Jotun Thinner no.7 (Xylene)	Apply 2-3 coats with 15-20 minutes interval			<ul style="list-style-type: none"> ● Grey ● Black
		Launching time, min:	3 h	8 h	10 h
		Launching time, max*:	9 mth	9 mth	9 mth

*Under the condition that the boat is well protected or stored indoors.



APPLICATION

Surface preparation is key to a successful result. It is very important to degrease the surface with Jotun Thinner no 7 prior to application of Vinyl Primer Spray or Antipest. Make sure you apply enough film thickness (2-3 coats) to secure all-season performance. Aqualine Optima should be applied from 20-25 cm distance and in a 90 degree angle.

DRIVE PRIOR TO SUBMERSION



DRIVE AFTER ONE SEASON



WWW.JOTUN.COM

JOTUN IBERICA S.A.

I ESTÀTICA, 3 | POL. IND. SANTA RITA | 08755 - CASTELLBISBAL
(BARCELONA) | PHONE +34 937 711 800 |